

**e-STUDIO™ 5508A**

**e-STUDIO™ 6508A**

**e-STUDIO™ 7508A**

**e-STUDIO™ 8508A**

- > Black & White Multifunction Printer
- > Up to 85 PPM
- > Large Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Solutions Ready




# e-STUDIO™ 5508A/6508A/7508A/8508A

## Main Specifications

<b>Copy System</b>	Indirect Electrostatic Photographic Method/OPC/Laser Printing/Heat Roller Fusing
<b>Display</b>	9" Color WVGA Touch Screen Tilting Display
<b>Copy Speed</b>	55/65/75/85 PPM (LT)
<b>First Copy Out</b>	5.2/5.2/4.5/4.1
<b>Warm-Up Time</b>	Approx. 24/24/20/20 Seconds
<b>Copy Resolution</b>	600 x 600 dpi
<b>Stack Feed Bypass</b>	3.9" x 5.8" to 13" x 19", 12" x 47" Banner, Envelope
<b>Multiple Copying</b>	Up to 9,999 Copies
<b>Paper Capacity</b>	Standard 3,520 Sheets/Max. 6,020 Sheets (Tandem Drawer)
<b>Original Feed</b>	Standard 300-Sheet DSDf
<b>Scan Speed &amp; Weights</b>	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color), Simplex: 9.3-110 lb Index, Duplex: 9.3-110 lb Index
<b>Max. Original Size</b>	LD
<b>Paper Feed Sizes</b>	Drawers: 540 Sheets-ST-R to 12" x 18" Integral Tandem LCF 1,160 x 2 LT-Only Stack Feed Bypass: 120 Sheets-3.9" x 5.8" to 13" x 19", 12" x 47" Banner 2,500-Sheet Ext. LCF LT-Only Tandem LCF 1,160 Sheets x 2-16 lb Bond-140 lb Index Plus 540 Sheets x 2-16 lb Bond-140 lb Index Stack Feed Bypass: 120 Sheets-16 lb Bond-110 lb Cover Opt. 2,500-Sheet Ext. LCF LT-Only -16 lb Bond-140 lb Index Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
<b>Paper Weights</b>	
<b>Duplex</b>	
<b>Reproduction Ratio</b>	25% to 400%
<b>Max Duty Cycle</b>	Max. 520K/590K/660K/720K Month
<b>Weight</b>	Approx. 430 lb
<b>Approx. Dimensions</b>	37.6" (W) x 28.9" (D) x 48.3" (H)
<b>Toner Yield</b>	106,600 @ 5%
<b>Power Source</b>	120 Volts, 50/60 Hz, 16 Amps
<b>Power Consumption</b>	Maximum 2.0kW (120V)
<b>CPU</b>	Intel Atom™ 1.33 GHz (Dual-Core)
<b>Memory</b>	4GB
<b>Hard Disk Drive</b>	320GB Self-Encrypting Drive FIPS 140-2 Validated

## e-BRIDGE Next Print Specifications

<b>PDL</b>	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
<b>Print Speed</b>	55/65/75/85 PPM (LT)
<b>Print Resolution</b>	600 x 600 dpi, 2,400 x 600 dpi (With Smoothing), 1,200 x 1,200 dpi (2-bit) or 3,600 x 1,200 dpi (With Smoothing) PS Only
<b>Operating Systems</b>	Windows® Vista, Windows Server® 2008/R2, Windows® 7, 8, 8.1, 10, Windows Server® 2012/R2, Macintosh® (Mac OS X 10.6, 10.7, 10.8, 10.9, 10.10, 10.11), Unix®, Linux®
<b>Network Protocols</b>	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk® for Macintosh Environments
<b>Printing Protocols</b>	SMB, LPR/LPD, IPP (Ver.1.1) w/Authentication, AppleTalk PAP or EtherTalk™, Port 9100 (bi-directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
<b>Print Drivers</b>	Windows® Vista SP2 (32-bit, 64-bit), Windows Server® 2008 SP2 (32-bit, 64-bit), Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit, 64-bit), Windows® 8/8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows® 10 (32-bit, 64-bit), Mac OS® X 10.6.8, 10.7.4, 10.8, 10.9, 10.10, 10.11
<b>Interface</b>	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed) Optional
<b>Wireless Device</b>	802.11b/g/n, Wireless LAN, Optional Bluetooth
<b>Device Management</b>	AirPrint™, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple App Store or Google Play)
<b>Account Control</b>	TopAccess, EFMS 6.2 (e-BRIDGE Fleet Management Software)
<b>Accessibility Features</b>	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



## Security Features

User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408 EAL3+), IEEE2600.1, IEEE802.1X, Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp  
\*Compliant with IEEE2600.1 in High Security Mode.

## Environmental Stds. Certification

Energy Star (V2.0), EPEAT Gold, RoHS  
WHQL (Windows 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell, Citrix, SAP

## Scan Specifications

<b>Scan Speed</b>	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color)
<b>Scan Modes</b>	Standard: Full Color, Auto Color, Monochrome, Grayscale
<b>Scan Resolution</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
<b>File Formats</b>	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
<b>Image Compression</b>	Color/Grayscale: JPEG (High, Middle, Low)

## Facsimile Specifications

<b>Compatibility</b>	Super G3
<b>Data Compression</b>	MH/MR/MMR/JBIG
<b>Transmission Speed</b>	Approx. 3 Seconds Per Page
<b>Fax Modem Speed</b>	Up to 33.6 Kbps
<b>Memory Transmission</b>	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
<b>Scan Speed</b>	0.7 Seconds Per Page, Maximum 73 IPM

## e-Filing Specifications

<b>Operation Method</b>	Color Touch Screen Control Panel or Client PC
<b>Number of Boxes</b>	1 Public Box, 200 Private User Boxes
<b>Capacity of Boxes</b>	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

## Accessories (Options)

<b>Additional Paper Options</b>	Unicode Font Enabler	GS1007	
Large Capacity Feeder	MP2502	Embedded OCR Enabler	
<b>Finishing Options</b>	MJ1111	Single License	GS1080
50-Sheet Staple Finisher	MJ1112	Five Licenses	GS1085
Saddle-Stitch Finisher	MJ6106	Multi-Station Print Enabler	
Hole Punch Unit for MJ1111/MJ1112	KA6551	Single License	GS1090
Side Exit Tray	KN1103	Five Licenses	GS1095
Finisher Guide Rail		Advanced Scanning (ReRite)	GB1280V8
<b>Connectivity/Security Options</b>	GD1370	SharePoint Connector	GB1440
FAX Unit/2nd Line for FAX Unit	GN4020	Exchange Connector	GB1450
Wireless LAN/Bluetooth	GR9000	Google Drive Connector	GB1540
Bluetooth Keyboard	GR1250	<b>Miscellaneous Options</b>	
Accessory Tray	GR1260	Accessible Arm	KK2560
Panel 10-Key Option	GR1290	Harness Kit for Coin Controller	QG1280
Card Reader Holder	GS1010		
Meta Scan Enabler	GP1080		
IPsec Enabler			

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint and the AirPrint logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1.

## Corporate Office

9740 Irvine Blvd., Irvine, CA 92618  
Tel: 949-462-6000

## East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054  
Tel: 973-316-2700

## Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631  
Tel: 773-380-6000

## South

2037 Bakers Mill Rd., Dacula, GA 30019  
Tel: 678-546-9385

## West Coast

9740 Irvine Blvd., Irvine, CA 92618  
Tel: 949-462-6000

## Web Site

www.business.toshiba.com