TOSHIBA

©-STUDIO™2329A/2829A

- > Black & White Multifunction Printer
- > Up to 28 PPM
- > Small Workgroup
- > Copy, Print, Scan, Fax
- > Mobile Enabled

Improve the efficiency of busy workgroups with the new Toshiba e-STUDIO2329A/2829A. Multifunctionality has never been this simple and this powerful all at once. Precise black and white output is delivered at speeds up to 28 pages per minute with full color scans at up to 22 pages per minute. The Reversing Automatic Document Feeder (RADF) and Automatic Duplex Unit (ADU) allow for two-sided copying and printing. With standard network connectivity, paper sizes supported up to 11" x 17", and a maximum paper capacity of 1,700 sheets, the e-STUDIO2329A/2829A can help get your business running even smoother. A fax feature along with a unique e-BRIDGE Print & Capture application and wireless LAN support (802.11 b/g/n) allow access and sharing from a variety of devices by authorized users.



©-STUDIO 2329A/2829A

Specifications

Copying/Printing Process Indirect Electrostatic Photographic Method

Type Desktop

Original Scanning Method Contact Image Sensor (CIS) Resolution 2400 x 600 dpi (with Smoothing)

Gradation 256 Steps

Fixed Hard Platen, Optional 50-Sheet RADF (14-28 lb) **Original Platen Type**

Available Original Size ST-R to LD Available Paper Size Drawer: ST-R to LD

Stack Feed Bypass: ST-R, LT, LD, Envelope

Paper Supply Standard: Drawer (250 Sheets x 1)

Stack Feed Bypass (100 Sheets)

Max.: 1,700 (Optional 250 Sheets x 1, 550 Sheets x 2) Drawer: 17-20 lb (Including Optional Paper Sources) **Available Paper Weight**

> Stack Feed Bypass: 14-120 lb Index Auto Duplexing Unit: 17-20 lb

Face Down/Inner Tray Paper Exit

Warm-up Time Approx. 18 Seconds (Scanner Function Available

During Warm-Up)

Electronic Counter (Indication by LCD Display) Counter Memory 512 MB (PostScript 3 Option Includes 512 MB

Additional RAM)

Department Codes 100

Power Supply 115 Volts, 12 Amps **Power Consumption** Maximum: 1.5kW **TEC Value** 1.17/1.36 kWh/Week

Standard: Approx. 22.6" x 21.2" x 16" (W x D x H) **Dimensions**

With PFU: Approx. 23" x 22.2 x 20" (W x D x H)

Weight Approx. 59.4 lb

Special Features Energy Saver, Auto Sleep Mode, Department Code

Max Duty Cycle 64K Copies

Certifications Energy Star V3.0, EPEAT (GOLD) & WEE (Argentina

Model) + RoHS Compliant

Worldwide Safety Stds. UL, GS, CE, CDRH, SASO, IRAM, EAC, CCC

Black Toner Yield 17.5 Impressions @ 5%

Copy Specifications

Copying Speed 23/28 PPM **Original Scan Speed** 25 SPM (by Using RADF) Scan Resolution 600 x 600 dpi (for Copying) **First Copy Time** Less Than 6.5 Seconds

Original/Copy Size ST-R to LD

Original Mode Photo, Text/Photo, Text, Background Erase

Image Density Control Automatic/Manual (11 Steps) **Reproduction Ratio** Zoom: 25% to 400% in 1% Increments **Multiple Copying** Up to 999 Copies (Ten Key Input)

Special Features Department Codes (100) Interrupt, APS/AMS. Auto Job Start, Automatic Sort Mode, ID Card Copy,

One Touch Key (2)

Print Specifications

Printing Speed 23/28 PPM

Printing Resolution 2400 x 600 dpi (with Smoothing) Interface Standard: 10/100 Base-T, USB 2.0

Optional: 802.11 b/g/n

PDL PCL 6 Emulation, Optional: Genuine Adobe PostScript 3

(Includes 512 MB Additional RAM)

USB Direct Printing JPEG, TIFF, PDF (Only PDF created by MFP can be direct

printed unless PS3 option installed)

Support OS Windows 7, 8, 8.1, 10, 2008R2, 2012, 2012 R2, (WHQL),

CUPS PCL Unix, Linux 5.10.x, 6.5.x

Scan Specifications

Standard: 10/100 Base-T **Connection Type**

Optional: 802.11 b/g/n

Scanning Resolution 100/150/200/300/400/600 dpi

Scanning Speed 25 SPM (BW) at 600 dpi, 22 SPM (Color) @ 200 dpi,

13 SPM @ 300 dpi

Scan Agent Scan to File, SMB, FTP, Scan to Email, Scan to USB, TWAIN

Paper Handling

Reversing Automatic Document Feeder (RADF)

50 Sheets **Stack Capacity Original Setting** Face Up ST-R to LD **Original Paper Size Original Paper Weight** 14-28 lb

FAX Specifications (optional)

Super G3, G3 Compatibility **Image Format on PSTN** JBIG, MMR, MR, MH **Document Size** ST-R-LD

Modem Speed 33.6 kbps to 2.4 kbps (Automatic Fallback) Transmission Speed Approx. 3 Seconds

ITU-T T.30 **Communication Protocols**

Memory Transmission Max 256 Jobs, 220 Destinations/Job, 384 Pages/File

Options

Midwest

South

West Coast

Platen Cover KA2507 Reversing Automatic Document Feeder (RADF) MR3032 Paper Feed Unit (PFU) MY1043B Paper Feed Pedestal (PFP) KD1039B **Drawer Module** MY1044B Cabinet STAND2507 Fax Kit GD1360 PostScript - e-STUDIO2309A GA1350L PostScript - e-STUDIO2809A GA1350H Wireless LAN Module GN1100 Damp Heater (for Drum) MF2505U **Harness for Coin Controller** GQ1131







Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Tone yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries

Corporate Office 25530 Commercentre Drive, Lake Forest, CA 92630 Tel: 949-462-6000

East Coast 959 Route 46 East, 5th Floor, Parsippany, NJ 07054

Tel: 973-316-2700

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631

Tel: 773-380-6000

2037 Bakers Mill Rd., Dacula, GA 30019

Tel: 678-546-9385

25530 Commercentre Drive, Lake Forest, CA 92630

Tel: 949-462-6000 Web Site www.business.toshiba.com